

Package: echo (via r-universe)

September 17, 2024

Title Echo Code Evaluations

Version 0.1.0.9000

Maintainer Jordan Mark Barbone <jmbarbone@gmail.com>

Description Capture code evaluations and script executions by expressions, outputs, and condition calls for logging.

License MIT + file LICENSE

Depends R (>= 3.6)

Imports utils

Suggests covr, spelling, testthat (>= 3.0.0)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

URL <https://github.com/jmbarbone/echo>,
<https://jmbarbone.github.io/echo/>

BugReports <https://github.com/jmbarbone/echo/issues>

Language en-US

Config/testthat/edition 3

Repository <https://jmbarbone.r-universe.dev>

RemoteUrl <https://github.com/jmbarbone/echo>

RemoteRef HEAD

RemoteSha a525e423e3923235131b59a5006bc45bb90ddac6

Contents

echo	2
Index	4

echo

Echo

Description

Echo expression or a file

Usage

```
echo(  
  expr,  
  log = echo_get_log(),  
  msg = echo_get_msg(),  
  level = echo_get_level(),  
  file = NULL  
)
```

Arguments

expr	Expression to evaluate; should be written with curly braces (see examples)
log	A connection or file name for outputs; defaults to <code>stdout()</code>
msg	Logical, if FALSE does not output a message; defaults to TRUE
level	Sets the echo level (see details); defaults to <code>0L</code>
file	File path to evaluate (like <code>base::source()</code>). If file is not NULL, then expr must be missing ⁴

Details

Levels of output can be controlled with level:

- 0 EXP: logs expressions that were evaluated
- 1 OUT: logs outputs from expressions
- 2 MSG: logs messages
- 3 WRN: logs warnings
- 4 ERR: logs errors

When set, all outputs at the level or below are run. Errors are always logged as they will interrupt and stop the program.

Timestamps are printed in UTC by default. To control this, set the option value, such as `options(echo.timezone = "EST")`.

Value

Nothing, called for side-effects

Examples

```
# make sure to use braces for expr
echo(letters, level = 0) # bad
echo({letters}, level = 0) # good

try(echo(
  expr = {
    print(1 + 1)
    Sys.sleep(2)
    head(mtcars)
    message(1)
    warning(2)
    stop(3)
  },
  level = 0
))

# Parse lines in a file instead
try(echo(file = system.file("example-script.R", package = "echo"))

# Note that
x <- c("example for", "writing lines")
echo({
  x
  print(x)
  writeLines(x)
}, level = 0)
```

Index

`base::source()`, 2

`echo`, 2